



mod. COU128BTPA | cod. 06625020

mod. COU128BTPRA | cod. 06625030







EN TECHNICAL SPECIFICATIONS

te	Available emperature (°C)	Dimensions W x D x H (mm)	Packaging dimensions W x D x H (mm)	Refrigerant gas	Net volum (L)	Climate class	Energy class	Power consumption (W)	11,	Annual consumption (kWh/anno)
	-18/-22	1280 x 700 x 900	1370 x 750 x 1100	R290	192	5	D	490	230 V / 50 Hz	2555

EN TECHNICAL AND FUNCTIONAL FEATURES

- Refrigerated counter with AISI 304 stainless steel worktop with splashback h 100 mm
- Structure entirely in steel. Interior, walls and door in AISI 304 stainless steel
- Motor inside the technical compartment
- Forced ventilated refrigeration with protected evaporators positioned between the compartments
- 60 mm insulation of high pressure injected HFO polyurethane with a density of 42 kg/m³
- ullet Tested with external working environment temperatures up to 43 °C, efficiency equivalent to energy class 5
- Automatic defrosting with electric resistance
- Automatic evaporation of condensate water by means of a copper heat exchanger
- Internal dimensions GN 1/1
- Door hinges with automatic closing system
- Easily removable magnetic door and drawer gaskets
- Rounded internal corners and removable parts to facilitate cleaning
- Temperature detection by means of a thermistor sensor (NTC probe)
- Evaporator painted for cataphoresis with high corrosion resistance
- Height-adjustable stainless steel feet

COU128BTPRA - cod. 06625030: version with round edge worktop

OPTIONAL

- Stainless steel grid GN 1/1
- · Stainless steel couple of "U" runners
- Set of 4/6 castors
- · Lock with key
- · Sink above the unit
- Neutral drawer above the unit
- Spare drawers' kit (1/2+1/2 1/3+2/3 1/3+1/3+1/3)

