


mod. **COU174BTPA** | cod. 06645020

mod. **COU174BTPRA** | cod. 06645030



**EN TECHNICAL SPECIFICATIONS**

Available temperature (°C)	Dimensions W x D x H (mm)	Packaging dimensions W x D x H (mm)	Refrigerant gas	Net volum (L)	Climate class	Energy class	Power consumption (W)	Supply voltage	Annual consumption (kWh/anno)
<b>-18 / -22</b>	1740 x 700 x 900	1800 x 750 x 1100	R290	288	5	E	570	230 V / 50 Hz	3376

**EN TECHNICAL AND FUNCTIONAL FEATURES**

- Refrigerated counter with AISI 304 stainless steel worktop with splashback h 100 mm
- Structure entirely in steel. Interior, walls and door in AISI 304 stainless steel
- Motor inside the technical compartment
- Forced ventilated refrigeration with protected evaporators positioned between the compartments
- 60 mm insulation of high pressure injected HFO polyurethane with a density of 42 kg/m<sup>3</sup>
- Tested with external working environment temperatures up to 43 °C, efficiency equivalent to energy class 5
- Automatic defrosting with electric resistance
- Automatic evaporation of condensate water by means of a copper heat exchanger
- Internal dimensions GN 1/1
- Door hinges with automatic closing system
- Easily removable magnetic door and drawer gaskets
- Rounded internal corners and removable parts to facilitate cleaning
- Temperature detection by means of a thermistor sensor (NTC probe)
- Evaporator painted for cataphoresis with high corrosion resistance
- Height-adjustable stainless steel feet

**OPTIONAL**

- Stainless steel grid GN 1/1
- Stainless steel couple of “U” runners
- Set of 4/6 castors
- Lock with key
- Sink above the unit
- Neutral drawer above the unit
- Spare drawers' kit  
(1/2 + 1/2 - 1/3 + 2/3 - 1/3 + 1/3 + 1/3)

COU174BTPRA - cod. 06645030: version with round edge worktop

