


	n.	2
	mm	300 x 300
	kW	3,5
	TOT kW	7
	VOLT	380-415 V3N~ 50/60 Hz
	kg	56



OPTIONAL

PG2Q900 Piastra in ghisa / Cast iron plate / Plaque en fonte / Gusseisenplatte

1P DX Porta con maniglia spessore 20/10 / Door with handle of 20/10 thickness / Porte avec poignée épaisseur 20/10 / Tür mit Griff Stärke 20/10

V3/A Volts 220 - 240 3~

CARATTERISTICHE TECNICHE E FUNZIONALI

Piano di lavoro e pannelli frontali in acciaio inox AISI 304, finitura Scotch Brite. Piano stampato in un pezzo unico a tenuta stagna. Piastre in ghisa con termostato di sicurezza e selettore a 6 posizioni che attiva 6 diverse zone concentriche di potenza.

TECHNICAL AND FUNCTIONAL FEATURES

Worktop and front panels made of AISI 304 stainless steel and Scotch Brite finishing. Pressed top in a unique sealed piece. Cast iron plates with safety thermostat and 6-position selector that activates 6 different concentric power zones.

CARACTÉRISTIQUES TECHNIQUES ET FONCTIONNELLES

Plan de travail et panneaux frontaux en acier inoxydable AISI 304, finition Scotch Brite. Plan de cuisson étanche moulé d'une seule pièce. Plaques en fonte avec thermostat de sécurité et sélecteur à 6 positions qui active 6 différentes zones concentriques de puissance.

TECHNISCHE UND FUNKTIONELLE EIGENSCHAFTEN

Arbeitsfläche und Vorderfront aus rostfreiem Edelstahl AISI 304, Ausführung Scotch Brite. In einem Stück formgestanztes hermetisches Kochfeld. Platten aus Gusseisen mit Sicherheitsthermostat und Wählschalter mit 6 verschiedenen konzentrischen Leistungsstufen.

E

connessione elettrica - electric connection
branchement électrique - Elektrischer Anschluss

380-415 V3N~

kW 7

