


	n.	1	1	2
	Ø mm	80	108	130
	kW	3,5	7	12
	kcal/h	3.010	6.020	10.320
	Btu/h	11.942	23.884	40.944
	kW	34,5		
	kcal/h	29.670		
	Btu/h	117.714		
	G30/G31	kg/h	2,72	
	G20	m³/h	3,65	
	G25	m³/h	4,25	
	Kg	104		



OPTIONAL
2P 400 2 porte con maniglia spessore 20/10 / 2 doors with handle of 20/10 thickness / 2 portes avec poignée de épaisseur 20/10 / 2 Türen mit Griff Stärke 20/10

CARATTERISTICHE TECNICHE E FUNZIONALI

Piano di lavoro e pannelli frontali e laterali in acciaio inox AISI 304. Interno AISI 430.
 Bruciatori in ghisa da 80 mm, con regolazione fino a 3,5 kW, da 108 mm, con regolazione fino a 7 kW e da 130 mm, con regolazione fino a 12 kW. Valvola di sicurezza a termocoppia e fiamma pilota protetta.
 Bacinelle stampate in acciaio inox AISI 304.

TECHNICAL AND FUNCTIONAL FEATURES

Worktop, front and side panels made of AISI 304 stainless steel. Inside AISI 430.
 Cast iron burners with thermocouple safety valve and protected pilot flame with regulation up to 3,5 kW on the 80 mm version, regulation up to 7 kW on the 108 mm version and regulation up to 12 kW on the 130 mm version. Pressed trays from AISI 304 stainless steel.

CARACTÉRISTIQUES TECHNIQUES ET FONCTIONNELLES

Plan de travail et panneaux frontaux et latéraux en acier inoxydable AISI 304. Intérieur inox 430.
 Brûleurs en fonte de 80 mm, réglable jusqu'à 3,5 kW, de 108 mm, réglable jusqu'à 7 kW et de 130 mm, réglable jusqu'à 12 kW. Soupape de sécurité à thermocouple et flamme pilote protégée.
 Cuves moulées en acier inoxydable AISI 304.

TECHNISCHE UND FUNKTIONELLE EIGENSCHAFTEN

Arbeitsfläche, Vorder- und Seitenwände aus rostfreiem Edelstahl AISI 304. Innen AISI 430.
 Brenner aus Gusseisen d 80 mm mit Einstellung bis 3,5 kW, d 108 mm mit Einstellung bis 7 kW und d 130 mm mit Einstellung bis 12 kW.
 Sicherheitsventil mit Thermoelement und geschützter Zündflamme.
 Gestanzte Mulden aus rostfreiem Edelstahl AISI 304.

G connessione gas - gas connection
 branchement gaz - Gasanschluß R 1/2 UNI ISO 7/1 **KW 34,5**

