


	n.	6
	mm	300 x 300
	kW	3,5
	TOT	kW 21
	VOLT	380-415 V3N~ 50/60 Hz
	kg	136



**OPTIONAL**

- PG2Q900** Piastra in ghisa / Cast iron plate / Plaque en fonte / Gusseisenplatte
- 2P 600** 2 porte con maniglia spessore 20/10 / 2 doors with handle of 20/10 thickness / 2 portes avec poignée de épaisseur 20/10 / 2 Türen mit Griff Stärke 20/10
- V3/B** Volts 220 - 240 3~

**CARATTERISTICHE TECNICHE E FUNZIONALI**

Piano di lavoro e pannelli frontali in acciaio inox AISI 304, finitura Scotch Brite. Piano stampato in un pezzo unico a tenuta stagna. Piastre in ghisa con termostato di sicurezza e selettore a 6 posizioni che attiva 6 diverse zone concentriche di potenza.

**TECHNICAL AND FUNCTIONAL FEATURES**

Worktop and front panels made of AISI 304 stainless steel and Scotch Brite finishing. Pressed top in a unique sealed piece. Cast iron plates with safety thermostat and 6-position selector that activates 6 different concentric power zones.

**CARACTÉRISTIQUES TECHNIQUES ET FONCTIONNELLES**

Plan de travail et panneaux frontaux en acier inoxydable AISI 304, finition Scotch Brite. Plan de cuisson étanche moulé d'une seule pièce. Plaques en fonte avec thermostat de sécurité et sélecteur à 6 positions qui active 6 différentes zones concentriques de puissance.

**TECHNISCHE UND FUNKTIONELLE EIGENSCHAFTEN**

Arbeitsfläche und Vorderfront aus rostfreiem Edelstahl AISI 304, Ausführung Scotch Brite. In einem Stück formgestanztes hermetisches Kochfeld. Platten aus Gusseisen mit Sicherheitsthermostat und Wählschalter mit 6 verschiedenen konzentrischen Leistungsstufen.

<b>E</b>	connessione elettrica - electric connection branchement électrique - Elektrischer Anschluss	380-415 V3N~	<b>kW 21</b>
----------	--	--------------	--------------

